ENERGY SAVING WEATHER BLANKET® INSULATION

Insulation Certificate

WEATHER BLANKET CELLULOSE INSULATION

Date: _____
To: _____
Address: _____
City, State: _____

Ceilings _____sq. ft. _____BAGS INSTALLED
Walls _____sq. ft. _____BAGS INSTALLED
Other _____sq. ft. _____BAGS INSTALLED

Weather Blanket insulation has been manufactured to meet CPSC Interim Safety Standard (16 CFR Part 1209) characteristics, Type 1, in accordance with test methods and procedures of ASTM - C-739.

Each bag of Weather Blanket Insulation is R&D Services, Inc. classified and an R&D Services, Inc. classification mark as shown below appears on every bag.

LISTED
RDS-LF9755

Classified in accordance with the following UL 723, ASTM C-739 characteristics.

Flammability Characteristics

Critical Radiant Flux	Greater than or equal to 0.12 w/cm^2
Smoldering Combustion	Less than or equal to 15.0 percent

Tested at 1.2 pcf density

FLAME SPREAD	5
SMOKE DEVELOPED	50

Environmental Characteristics

Corrosiveness	Acceptable
Fungi Resistance	Acceptable

Physical Characteristics

Density (Settled)	1.4 pcf
Thermal Resistance	3.75 R/in. (at 4 in. thickness)
Moisture Absorption	Acceptable
Odor Emission	Acceptable

Installer: _____
Address: _____
City, State: _____

Weather Blanket Insulation
1249 S. Hickory Street, Fond du Lac, WI 54937
1206 S. Monroe Street, Spencer, WI 54479